

Generator set data sheet



Model: C66D5E
Frequency: 50Hz
Fuel type: Diesel
kW rating: 53 Standby
 48 Prime

Emissions level: EU Stage IIIA

| | |
|---------------------------------|---------------------|
| Exhaust emission data sheet: | |
| Sound performance data sheet: | |
| Cooling performance data sheet: | |
| Genset outline: | A058W348 / A059Y944 |

| Fuel consumption | Standby | | | | Prime | | | | Continuous | | | |
|------------------|----------|-----|------|------|----------|-----|-----|------|------------|-----|-----|------|
| | kW (kVA) | | | | kW (kVA) | | | | kW (kVA) | | | |
| Ratings | 53 (66) | | | | 48 (60) | | | | | | | |
| Load | 1/4 | 1/2 | 3/4 | Full | 1/4 | 1/2 | 3/4 | Full | 1/4 | 1/2 | 3/4 | Full |
| US gph | 1,1 | 2,1 | 3,2 | 4,2 | 1,1 | 2,1 | 2,9 | 4,0 | | | | |
| L/h | 4,0 | 8,0 | 12,0 | 16 | 4 | 8 | 11 | 15 | | | | |

| Engine | Stanby rating | Prime rating | Continuous rating |
|--------------------------------------|--------------------|--------------|-------------------|
| Engine manufacturer | Cummins Inc. | | |
| Engine model | 4BTAA3.3-G14 | | |
| Configuration | 4-Cylinder | | |
| Aspiration | Turbocharged e CAC | | |
| Gross engine power output, kWm (bhp) | 63 (84) | 58 (78) | |
| BMEP at set rated load, kPa (psi) | 1538 (223) | 1428 (207) | |
| Bore, mm (in.) | 95 (3,74) | | |
| Stroke, mm (in.) | 115 (4,53) | | |
| Rated speed, rpm | 1500 | | |
| Piston speed, m/s (ft/min) | 5,75 (1132) | | |
| Compression ratio | 19,0 : 1 | | |
| Lube oil capacity, L (qt) | 7,9 (2,1) | | |
| Overspeed limit, rpm | 1800±50 | | |

Fuel flow

| | |
|---------------------------------------------------|-----------|
| Maximum fuel flow, L/hr (US gph) | 45 (12) |
| Maximum fuel inlet restriction, kPa (in Hg) | 7,9 (2,1) |
| Maximum fuel inlet temperature, °C (°F) | 70 (158) |
| Maximum fuel return line restriction, kPa (in Hg) | 10,16 (3) |

| Air | Standby rating | Prime rating | Continuous rating |
|-----------------------------------------------|----------------|--------------|-------------------|
| Combustion air, CFM (L/s) | 175,87 (83) | 158,92 (75) | |
| Maximum air cleaner restriction, kPa (in H2O) | 6,23 (25) | | |
| Alternator cooling air, m³/min (cfm) | 458 (50) | | |

Exhaust

| | | | |
|-------------------------------------------|--------------|--------------|--|
| Exhaust flow at set rated load, CFM (L/s) | 461,92 (218) | 411,06 (194) | |
| Exhaust temperature, °C (°F) | 497 (926) | 492 (916) | |
| Maximum back pressure, kPa (in H2O) | 6,23 (25) | | |

Standard set-mounted radiator cooling

| | | | |
|-----------------------------------------------------------|-------------|-------------|--|
| Ambient design, °C (°F) | 50 (122) | | |
| Fan load, kWm (HP) | 2 (2,68) | | |
| Coolant capacity (with radiator), L (US gal) | 12,2 (3,22) | | |
| Cooling system air flow, m³/min (scfm) | 96,66 (2,6) | | |
| Total heat rejection, MJ/min (Btu/min) | 1,98 (1877) | 1,83 (1734) | |
| Maximum cooling air flow static restriction, kPa (in H2O) | 0,25 (1) | | |

Optional with TransferSwitch integrated

| | |
|--------------------------------------|------|
| Nominal Current (A) for 220V at 60°C | 250 |
| Insulation Voltage (V) for 220V | 1000 |
| Current Open capacity (kA) for 440V | 1100 |
| Nominal Current (A) for 380V At 60°C | 125 |
| Insulation Voltage (V) for 380V | 760 |
| Current Open capacity (kA) for 440V | 880 |

Weights

| | |
|-------------------------------|------|
| Unit Open dry weight, kgs | 901 |
| Unit Open wet weight, kgs | 921 |
| Unit Enclosed dry weight, kgs | 1208 |
| Unit enclosed wet weight, kgs | 1228 |

Derating factors

| | |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standby | Full rated power available up to 3200 m (10499 ft) elevation at ambient temperatures up to 40 °C (104 °F). Above these conditions derate by 2,2% per 300 m (1000 ft), and derate by an additional 7,3% per 10 °C (18 °F). |
| Prime | Full rated power available up to 2600 m (8530 ft) elevation at ambient temperatures up to 50 °C (122 °F). Above these conditions derate by 2,4% per 300 m (1000 ft), and derate by an additional 8% per 10 °C (18 °F) |
| Continuous | - |

Ratings definitions

| Emergency Standby Power (ESP): | Limited-Time Running Power (LTP): | Prime Power (PRP): | Base Load (Continuous) Power (COP): |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. Emergency Standby Power (ESP) is in accordance with ISO 8528. Fuel stop power in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514. | Applicable for supplying power to a constant electrical load for limited hours. Limited-Time Running Power (LTP) is in accordance with ISO 8528. | Applicable for supplying power to varying electrical load for unlimited hours. Prime Power (PRP) is in accordance with ISO 8528. Ten percent overload capability is available in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514. | Applicable for supplying power continuously to a constant electrical load for unlimited hours. Continuous Power (COP) is in accordance with ISO 8528, ISO 3046, AS 2789, DIN 6271 and BS 5514. |

Alternator data

| Voltage | Connection | Temp rise degrees C | Duty¹ | Winding No. | Frame size |
|----------------|-------------------|----------------------------|-------------------------|--------------------|-------------------|
| 220 | Wye, 3Phase | 150 | S/P | 311 | UC224F |
| | | | | | |
| | | | | | |
| 380 | Wye, 3Phase | 150 | S/P | 311 | UC224F |

Notes:

¹ Standby (S), Prime (P) and Continuous ratings (C).

Formulas for calculating full load currents:

Three phase output

$$\frac{\text{kW} \times 1000}{\text{Voltage} \times 1.73 \times 0.8}$$

Warning: Back feed to a utility system can cause electrocution and/or property damage. Do not connect to any building's electrical system except through an approved device or after building main switch is open.

**For more information contact your local Cummins distributor
or visit power.cummins.com**



Our Energy working for you.™

©2019 Cummins Inc. All rights reserved. Cummins is a registered trademark of Cummins Inc. PowerCommand, AmpSentry, InPower and "Our energy working for you." are trademarks of Cummins Inc. Other company, product, or service names may be trademarks or service marks of others. Specifications are subject to change without notice.